

Tung Oil

The best natural wood finish

We proudly present the best wood finish, completely **natural** and **renewable** comes from the nut of the Tung tree, it is not only save and environmentally friendly but also produces a beautiful result on any type of wood.

The oil is called Tung Oil. It is usually applied to unfinished wood, but can be used over oil base stain. It is easy to use and has the ability to dry quickly and polymerize into a tough, glossy, waterproof coating. This property has made it especially valuable in paints, waterproof coatings and lustrous wood finishes. This product is available in 1 liter can, 5 liter can or more (customized).

Apply oil to a soft cloth or rag and rub thinly on the surface for a maximum of 10 minutes, and then wipe all areas clean to remove excess. Check for any pools or runs after another few minutes and wipe them dry. Drying is a slow process and will occur over 12-24 hours. You can apply up to 6 coats for super deep resistant finish, but a normal treatment is 2 or 3 coats for flooring, wall panels can be just 2 coats. For best results use cotton socks when reapplying coats, and allow the floor to dry for 7 days before traffic. The floor can be walked on after 2 days, as long as you use socks.

Maintenance is very easy. Light scratches can be removed with light sanding and the addition of another coat of Tung Oil finish. Interior wood surfaces might need another coat every 2-4 years and exterior wood 1-2 years, depending on exposure to sun light and wood species.

For deeper penetration it can be thinned up to 50% with citrus solvent, mineral spirits or turpentine. Thinning the first coat will increase the penetration, decrease the drying time and produce better results. The oil is applied by hand rubbing.



Features

- Easy to apply (rub on, rub off)
- Waterproof (or at least highly water resistant on a well maintained surface)
- Resistant to alcohol
- Resistant to acetone (such as nail polish or remover)
- Resistant to fruit acids and vegetable acids (such as orange juice)
- Flexible. Oil finishes continue to protect as the wood expands and contract.
- Easy to re-apply if the original finish becomes worn or damaged
- Non-toxic and food-safe (In pure form only! Be careful!)