



COLDGLAZE 1.2

A water based 100% non - plasticized ASA Acrylic for surface sealer applications.

Coldglaze 1.2 is suitable as a protective sealer for use on most vertical and horizontal internal and external surfaces (indoor & outdoor).

Areas of application include roofs, walls, floors, paths, driveways, counter-tops and decorative items.

For optimum result and best protection, multiple coats should be applied 'wet on wet'.

*Contact our technical support team prior to use
(1st time user)*

SURFACES

Coldglaze 1.2 is suitable for any type of wood, bamboo, natural stone such as Granite, Limestone, as well as for Terrazzo and Concrete etc.

ADVANTAGES

Prevention Stain & Mold	Fast Drying
Environmentally Friendly	Non Toxic
Highly Adhesive	Durable
Low Odour	Preservation
Non Hazardous	Easy Cleaning

BASF
FORMULA



ecoSmart HUB

📍 Jl. Sunset Road 1 Kuta, Bali
📞 (+62) 361 752 133

✉️ info@ecosmarthub.com
🌐 www.ecosmarthub.com

COLDGLAZE 1.2 INSTRUCTION

1. Make Sure the Surface is DRY and clean before applying this product, light sanding requires to open the pores
2. Application can be use brush or other application tools
3. Do a small trial area and observe for 48 hours, to ensure that the result is based on expectation, especially for terracotta and other porous surfaces with potential of raising damp
4. Apply the Coldglaze 1.2 in a "wet on wet" way (one times for the first layer, then continue with second layer, don't wait the first layer to dry).
Leave it for 1x24 hours for maximum results.
5. Application on exterior exposed areas recommended to only do during dry season to avoid wash off and for maximum result as Coldglaze cures over 3 days in dry conditions.
6. There are no warranties on Coldglaze product supply, we recommend to do your own trials based on actual site conditions.

-
1. Pastikan permukaan yang akan diaplikasikan dalam keadaan KERING dan bersih (diperlukan pengamplasan halus pada permukaan sebelum aplikasi untuk membuka pori-pori)
 2. Aplikasikan dengan menggunakan kuas atau alat aplikasi lainnya
 3. Lakukan percobaan pada area kecil terlebih dahulu dan observasi selama 48 jam, untuk memastikan bahwa hasil sesuai dengan keinginan, khususnya untuk terakota dan permukaan berpori lainnya yang berpotensi menimbulkan kelembapan
 4. Aplikasikan Coldglaze 1.2 dengan cara "Wet on Wet" (satukali kuas untuk layer pertama, lalu dilanjutkan layer kedua, jangan sampai menunggu kering untuk layer pertama). Tunggu selama 1x24 jam untuk hasil yang lebih maksimal.
 5. Aplikasikan pada bagian eksterior yang terbuka, rekomendasi pengaplikasian pada musim kemarau agar tidak luntur dan hasil maksimal memerlukan waktu 3 hari dalam kondisi kering.
 6. Tidak ada garansi atas produk Coldglaze, kami menyarankan customer untuk melakukan uji coba berdasarkan kondisi area masing-masing.